

PAAR-TRONIC-LI-2YCYV PE-insulated, low capacitance, Termi-Point®, EMC-preferred type, meter marking

B



Technical data

- PE-insulated data cable
- **Temperature range**
flexing -5 °C to +70 °C
fixed installation -30 °C to +80 °C
- **Conductor resistance** (loop) at 20 °C
0,22 mm² max. 186 Ohm/km
0,34 mm² max. 115 Ohm/km
0,5 mm² max. 78,5 Ohm/km
1,0 mm² max. 39,2 Ohm/km
- **Operating top level voltage**
max. 250 V (not for purposes of high current and power installation)
- **Test voltage**
core/core 2000 V
core/screen 1000 V
- **Insulation resistance** min. 5 GOhm x km
- **Mutual capacitance** at 800 Hz
>4 pairs max. 60 nF/km
≤4 pairs values extended by 20%
- **Impedance** 100 Ohm ±15
- **Line attenuation** (approx. value)
0,22 mm² at 100 kHz 9,0 dB/km
0,34 mm² at 100 kHz 6,6 dB/km
0,50 mm² at 100 kHz 6,0 dB/km
0,22 mm² at 1 MHz 25,0 dB/km
0,34 mm² at 1 MHz 20,0 dB/km
0,50 mm² at 1 MHz 18,0 dB/km
- **Inductance** approx. 0,66 mH/km
- **Cross-talk attenuation**
up 1 MHz min. 50 dB
up 10 MHz min. 40 dB
- **Minimum bending radius**
flexing 12x cable ø
fixed installation 7,5x cable ø

Cable structure

- Bare copper stranded wires, 7-wires, adapted to DIN VDE 0881, suitable for Termi-Point® and solder-free connection technique
- Conductor make-up
0,22 mm² = 7x0,20 mm
0,34 mm² = 7x0,25 mm
0,5 mm² = 7x0,30 mm
- Core insulation of PE, compound type2Y11 to DIN VDE 0207 part 2
- Core colours to DIN 47100 with colour repetition
- Cores stranded in pairs with optimal lay-length
- Pairs stranded in layers with optimal lay-length
- Core wrapping with foil
- Tinned copper braided screening, coverage approx. 85%
- Special PVC outer sheath YM2 black, to DIN VDE 0207 part 5
- Type . . . Yv with reinforced outer sheath
- with meter marking, change-over in 2011

Properties

- PVC outer sheath self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- These cables make enormous advantages possible for fast and cost-effective contact-making using the Termi-Point® connection technique. With this solder-free connection technique, the stranded conductor is crimped together with a sleeve onto a contact pin without prior stripping of the insulation material
- The twisted-pair lay-up prevents electrical unbalances within the cable and this thus effectively suppresses cross-talking effects
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- At 0,22 mm² is designed for applications with Sub-D connectors.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- Termi-Point® registered trade mark AMP.
- To optimise the EMC features we recommend a large round contact of the copper braiding on both ends.

Application

These PE-insulated data cables with twisted pairs are used in particular for the interference-free transmission of data and signals over longer distances. The high transmission rates are particularly suitable for RS 422 and RS 485 interfaces. These cables are suitable for fixed installations as well as for flexing applications, for free movement without forced motion and without tensile stress, in dry and moist environments. Yv black with reinforced outer sheath, is suitable for installation in the ground and in open air.

EMC = Electromagnetic compatibility

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No.pairs x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No.pairs x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
21129	2 x 2 x 0,22	8,0	26,0	60,0	24	21141	2 x 2 x 0,5	10,0	49,0	90,0	20
21130	3 x 2 x 0,22	8,3	31,0	79,0	24	21142	3 x 2 x 0,5	10,4	60,0	126,0	20
21131	4 x 2 x 0,22	8,9	38,0	96,0	24	21143	4 x 2 x 0,5	11,2	73,0	146,0	20
21132	8 x 2 x 0,22	10,6	62,0	140,0	24	21144	8 x 2 x 0,5	13,9	124,0	246,0	20
21133	10 x 2 x 0,22	12,1	79,0	184,0	24	21145	10 x 2 x 0,5	16,0	155,0	292,0	20
21135	2 x 2 x 0,34	9,2	35,0	83,0	22	21146	2 x 2 x 1	10,8	81,0	141,0	17
21136	3 x 2 x 0,34	9,6	44,0	92,0	22	21147	3 x 2 x 1	11,5	102,0	170,0	17
21137	4 x 2 x 0,34	10,2	53,0	112,0	22	21148	4 x 2 x 1	12,0	130,0	203,0	17
21138	8 x 2 x 0,34	12,8	86,0	179,0	22	21149	8 x 2 x 1	14,9	240,0	261,0	17
21139	10 x 2 x 0,34	14,1	104,0	219,0	22	21150	10 x 2 x 1	17,2	282,0	287,0	17

Dimensions and specifications may be changed without prior notice.